

StorFly® 2.5-Inch SATA Solid-State Drive

Series 6 (Gen2), SATA-III (6Gb/s), pSLC

VSFF25XI240G-V11

Product Brief - Rev. 1.0 See Datasheet for all details



Description

Virtium's StorFly[®] Series 6 2.5" is high-performance SATA-III 6Gb/s embedded solid-state drive (SSD) technology designed for the unique capacity and workload requirements of a broad range of embedded systems, including telco and networking, industrial PC and automation, test and measurement, medical diagnostics and imaging, transportation, defense command and control, self-serve kiosk and POS, security and surveillance, and data recorders.

Features

Capacity

• 240 GB

pSLC NAND

Sequential Performance

- 128kB Sequential Read: 550 MB/s (QD: 32)
- 128kB Sequential Write: 480 MB/s (QD: 32)

Random Performance

4kB IOPS Read: up to 72,000 (QD: 32)4kB IOPS Write: up to 82,000 (QD: 32)

Power: 5.0V±10%

128kB Sequential Read: 2.10 W
128kB Sequential Write: 2.30 W
4kB Random Read: 2.00 W
4kB Random Write: 2.40 W

• Idle: 0.68 W

Temperature Ranges

Industrial: -40°C to 85°C
Non-Operating: -40°C to 85°C

Reliability

Advanced LDPC ECC

• MTBF: >2M hours

Endurance

JESD219A: 4,500 TBWSequential: 9,300 TBW

vtGuard® Power Fail Protection

- Integrated power fail protection
- Preserves static data in the event of power failure
- Cache/buffer contents restored at power-on

SMART Attribute Reporting

- · Monitors device health
- Anticipates and predicts failures

Mechanical Dimensions

- 2.5-Inch Form Factor
- Length x Width x Height mm (inches)
 100.5 (3.96) x 69.85 (2.75) x 7.0 (0.275)

Compliance

- SATA Revision 3.1 (SATA-III 6Gb/s)
- ATA/ATAPI-8 (ACS-3)
- FCC, CE, UL, RoHS, WEEE

Environmental (Non-operating)

- Humidity (non-condensing): 5% to 95%
- Shock: 1500G, half-sine wave, 0.5ms duration
- Vibration: 20G, 20 Hz to 2000 Hz

Data Security

- Integrated AES-256 encryption (data-at-rest)
- · Crypto Erase
- TCG/ Opal 2.0-compliant SED(1)

StorKit® Software - visit virtium.com to learn more.

vtView[®], vtSecure[™], vtTools[™]



Electrostatic Discharge (ESD) can damage this device. When handling the device, always wear a grounded wrist strap and use a static dissipative surface.

Note: (1) Available in parts with -T part number extension



Any damage to the unit that occurs after its removal from the shipping package and ESD protective bag is the responsibility of the user.